



Adaptér s vnitřním závitem

- S výztužným kroužkem z nerez oceli (**AISI430**)
- Instalace bez demontáže
- Vhodné pro PE a PEX trubky
- Voda: PN16
- Materiál: PP
- Těsnění: NBR v kvalitě pro pitnou vodu
- Vnitřní závit: ISO 7 (paralelní)
- Barva: Modrá/černá

d	Rp	PN	Kód	SP	GP	Váha	D	L	L1	L2	L3
(mm)	(inch)	(bar)				(kg)	(mm)	(mm)	(mm)	(mm)	(mm)
16	½	16	158 400 355	1	75	0.047	44	74	46	19	15
20	½	16	158 400 088	1	220	0.043	45	75	54	19	15
20	¾	16	158 400 089	1	200	0.048	45	77	54	19	16
25	½	16	158 400 090	1	175	0.061	53	81	59	21	15
25	¾	16	158 400 091	1	175	0.065	53	81	59	21	16
25	1	16	158 400 092	1	150	0.075	53	87	59	21	20
32	¾	16	158 400 093	1	110	0.097	64	90	66	23	16
32	1	16	158 400 094	1	100	0.105	64	94	66	23	20
32	1 ¼	16	158 400 095	1	100	0.118	64	97	66	23	22
40	1	16	158 400 096	90	0	0.155	75	105	76	26	20
40	1 ¼	16	158 400 097	90	0	0.163	75	107	76	26	22
40	1 ½	16	158 400 098	90	0	0.172	75	108	76	26	22
50	1	16	158 400 099	45	0	0.281	97	117	88	30	20
50	1 ¼	16	158 400 100	45	0	0.286	97	119	88	30	22
50	1 ½	16	158 400 101	45	0	0.298	97	119	88	30	22
50	2	16	158 400 102	40	0	0.327	97	125	88	30	26
63	1 ½	16	158 400 103	25	0	0.491	114	137	104	35	22
63	2	16	158 400 104	25	0	0.515	114	141	104	35	26
63	2 ½	16	158 400 105	18	0	0.564	114	148	104	35	31
75	2	16	158 400 106	18	0	0.824	135	173	133	41	26
75	2 ½	16	158 400 107	18	0	0.758	135	178	133	41	31
75	3	10	158 400 108	16	0	0.925	135	183	133	41	34
90	2	16	158 400 109	8	0	1.277	161	192	150	44	26
90	2 ½	16	158 400 110	8	0	1.320	161	197	150	44	31
90	3	10	158 400 111	8	0	1.357	161	199	150	44	34
110	3	10	158 400 112	6	0	1.940	185	226	175	53	34
110	4	10	158 400 113	6	0	2.046	185	232	175	53	40

Přeloženo z originálu výrobce