



T-kus 90° s vnitřním závitem

- S výztužným kroužkem z nerez oceli (**AISI430**)
- Instalace bez demontáže
- Vhodné pro PE a PEX trubky
- Voda: PN16
- Materiál: PP
- Těsnění: EPDM v kvalitě pro pitnou vodu
- Vnitřní závit: ISO 7 (paralelní)
- Barva: modrá/černá

d	Rp	PN	Kód	SP	GP	Váha	D	L	L1	L2	L3	H
(mm)	(inch)	(bar)				(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
16	½	16	158 400 359	10	30	0.140	45	134	54	19	15	40
20	½	16	158 400 177	10	100	0.084	45	134	54	19	15	40
20	¾	16	158 400 178	10	100	0.086	45	134	54	19	16	41
25	½	16	158 400 179	10	80	0.114	53	150	19	21	15	40
25	¾	16	158 400 180	10	80	0.119	53	150	59	21	16	44
25	1	16	158 400 181	10	70	0.132	53	150	59	21	20	49
32	½	16	158 400 182	10	50	0.202	64	173	66	23	15	42
32	¾	16	158 400 183	10	50	0.190	64	173	66	23	16	46
32	1	16	158 400 184	10	50	0.213	64	173	66	23	20	54
32	1 ¼	16	158 400 185	10	50	0.214	64	173	66	23	22	57
40	¾	16	158 400 186	35		0.284	75	203	76	26	16	49
40	1	16	158 400 187	35		0.301	75	203	76	26	20	57
40	1 ¼	16	158 400 188	35		0.311	75	203	76	26	22	62
40	1 ½	16	158 400 189	35		0.327	75	206	76	26	22	63
50	1	16	158 400 190	22		0.553	97	239	88	30	20	61
50	1 ¼	16	158 400 191	22		0.570	97	239	88	30	22	66
50	1 ½	16	158 400 192	22		0.588	97	171	88	30	22	70
50	2	16	158 400 193	18		0.618	97	239	88	30	26	75
63	1 ¼	16	158 400 194	10		0.981	114	288	104	35	22	73
63	1 ½	16	158 400 195	10		0.900	114	288	104	35	22	76
63	2	16	158 400 196	10		1.047	114	207	104	35	26	83
75	2 ½	16	158 400 197	6		1.713	135	360	133	41	31	101
90	3	10	158 400 198	3		2.792	161	413	150	44	34	116
110	4	10	158 400 199	2		4.216	185	484	175	53	40	135

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems info@ppsengineering.cz

www.ppsengineering.cz

© PPS 11/2021