



340

Šroubení s kónickým sedlem, ISO/EN U11

- 374 G odkazuje na rozměr závitu G dle ISO 228 pro převlečnou matici 374
- * Vnitřní šestihran
- ** Varianta

EN	Dim.	** 374 G	Černé	Galvanizované	SP	GP	a	z1	s1	s2	s3
	(inch)	(inch)	kód	kód			(mm)	(mm)	(mm)	(mm)	(mm)
•	1/8	1/2	770 340 101	770 340 201	0	80	38	24	15	26	15
•	1/4	5/8	770 340 102	770 340 202	0	60	42	22	19	28	*10
•	3/8	3/4	770 340 103	770 340 203	10	40	48	28	22	32	*12
•	1/2	1	770 340 104	770 340 204	10	70	48	22	26	41	25
•	1/2	s 1 1/8	770 340 120	770 340 220	0	50	48	22	26	44	26
•	3/4	1 1/4	770 340 105	770 340 205	10	50	52	22	31	48	32
•	1	1 1/2	770 340 106	770 340 206	0	30	58	24	38	55	38
•	1 1/4	2	770 340 107	770 340 207	0	20	65	27	48	67	48
•	1 1/2	2 1/4	770 340 108	770 340 208	0	15	70	32	54	74	54
•	2	2 3/4	770 340 109	770 340 209	0	10	78	30	66	90	66
•	2 1/2	3 1/2	770 340 110	770 340 210	0	5	90	36	85	111	85
•	3	4	770 340 111	770 340 211	0	4	101	41	96	130	96
•	4	5	770 340 112	770 340 212	0	4	114	42	120	151	120

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 01/2019