




Přechodová tvarovka SYGEF Ultra pro spoj Flare PN16

Vysoce čistý produkt pro čisté prostory ISO třída 5

Provedení:

- Materiál: PEEK-HP



d (mm)	DN (mm)	PN (bar)	kód	Váha (kg)	Bm1 (mm)	DE2 (mm)	FM	Lmax (mm)	s (mm)	Vhodné pro
20	15	16	736 598 006	0.015	30.0	20.5	IR	74.6	1.9	1/4"
25	20	16	736 598 007	0.017	30.0	20.5	IR	74.6	1.9	1/4"
20	15	16	736 598 016	0.017	30.0	23.1	IR	76.2	1.9	3/8"
25	20	16	736 598 017	0.019	30.0	23.1	IR	76.2	1.9	3/8"
25	20	16	736 598 026	0.019	30.0	26.2	IR	76.5	1.9	1/2"
20	15	16	736 598 027	0.021	30.0	26.2	IR	76.5	1.9	1/2"
32	25	16	736 598 028	0.024	30.0	26.2	IR	76.5	1.9	1/2"
20	15	16	736 598 036	0.033	29.7	33.8	IR	77.6	1.9	3/4"
25	20	16	736 598 037	0.030	30.0	33.8	IR	77.6	1.9	3/4"
32	25	16	736 598 038	0.032	30.0	33.8	IR	77.6	1.9	3/4"
25	20	16	736 598 047	0.066	30.3	45.7	IR	87.3	1.9	1"
32	25	16	736 598 048	0.060	30.3	45.7	IR	87.3	1.9	1"

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 10/2026