



Šroubení PROGEF Plus PN10

Provedení:

- Materiál: **PP-H**
- Polyfúzní svařování metric
- d75-110 s novou závitovou geometrií, nyní nominální tlak PN10 až do d110
- Těsnící plocha: s O-kroužkem
- Čištěné a dvojité balené

d (mm)	PN (bar)	EPDM kód	Váha (kg)	FKM kód	Váha (kg)
16	10	727 510 255	0.020	727 520 255	0.020
20	10	727 510 256	0.041	727 520 256	0.039
25	10	727 510 257	0.064	727 520 257	0.063
32	10	727 510 258	0.079	727 520 258	0.079
40	10	727 510 259	0.137	727 520 259	0.137
50	10	727 510 260	0.135	727 520 260	0.180
63	10	727 510 261	0.251	727 520 261	0.312
75	10	727 510 292	0.427	727 520 292	0.432
90	10	727 510 293	0.617	727 520 293	0.625
110	10	727 510 294	1.161	727 520 294	1.009

d (mm)	L (mm)	L1 (mm)	D (mm)	G (inch)	z (mm)	z1 (mm)	Vel.	O-kroužek EPDM	O-kroužek FKM
16	24	18	35	3/4	5	11	15,54 x 2,62	748.413.005	749.413.005
20	26	19	48	1	5	12	20,22 x 3,53	748.413.006	749.413.006
25	28	21	58	1 1/4	5	12	28,17 x 3,53	748.413.007	749.413.007
32	30	23	65	1 1/2	5	12	32,93 x 3,53	748.413.008	749.413.008
40	34	25	79	2	5	14	40,65 x 5,54	748.413.009	749.413.009
50	39	28	91	2 1/4	5	16	47,00 x 5,34	748.413.010	749.413.010
63	47	32	111	2 3/4	5	20	59,69 x 5,34	748.413.011	749.413.011
75	51	36	135	S110 x 5	3	18	74,63 x 5,34	748.410.383	749.410.383
90	55	42	158	S130 x 5	5	18	94,62 x 5,34	748.410.248	749.410.248
110	54	49	188	S155 x 5	6	12	114,7 x 6,99	748.410.384	749.410.384

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 12/2023