



Trubka COOL-FIT 4.0 d32-d450

Provedení:

- Předizolovaný PE100 SDR11/17 metric
- Izolace: vysokohustotní pěna GF HE
- Vnější plášť: odolný proti nárazu a UV; Barva: černá
- Délka: 5 m pro d32-d225, 5.9 m pro d250-d450
- S volným koncem pro elektrotvarovku

d	d/D	DN	SDR	PN	Kód	Váha	di	L	L1	Nejbl. inch
(mm)	(mm)	(mm)		(bar)		(kg/m)	(mm)	(mm)	(mm)	(inch)
32	32/90	25	11	16	738 173 108	1.411	26.2	5000	36	1
40	40/110	32	11	16	738 173 109	2.054	32.6	5000	40	1 ½
50	50/110	40	11	16	738 173 110	2.221	40.8	5000	44	1 ½
63	63/125	50	11	16	738 173 111	2.987	51.4	5000	48	2
75	75/140	65	11	16	738 173 112	3.757	61.4	5000	55	2 ½
90	90/160	80	11	16	738 173 113	4.819	73.6	5000	62	3
110	110/180	100	11	16	738 173 114	6.200	90.0	5000	72	4
160	160/250	150	17	10	738 173 117	9.921	141.0	5000	90	6
225	225/315	200	17	10	738 173 120	16.620	198.2	5000	110	8
250	250/355	250	17	10	738 173 021	18.180	220.4	5900	123	10
280	280/400	250	17	10	738 173 022	22.640	246.8	5900	126	10
315	315/450	300	17	10	738 173 023	28.510	277.6	5900	133	12
355	355/500	350	17	10	738 173 024	35.350	312.8	5900	148	14
400	400/560	400	17	10	738 173 125	44.070	352.6	5900	150	16
450	450/630	450	17	10	738 173 126	55.490	396.6	5900	165	18

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 12/2021