




Ohyb 90° ecoFIT PE100
d50-500 mm / SDR 17

Provedení:

- Konvenční svařování natupo dle DVS 2207
- Kompatibilní pro IR = infračervené (IR Plus) svařování. Zvolte svařovací parametry: PE100



d	DN	PN	SDR	FM	Kód	Váha	PF	L	L1	R	e
(mm)	(mm)	(bar)				(kg)		(mm)	(mm)	(mm)	(mm)
50	40	10	17/17.6	IR	753 018 635	0.052	2 68 240 026	58	21	37.00	2.9
63	50	10	17/17.6	IR	753 018 636	0.087	2 68 240 026	66	21	45.00	3.6
75	65	10	17/17.6	IR	753 018 637	0.133	2 68 240 006	75	21	71.25	4.5
90	80	10	17/17.6	IR	753 018 638	0.226	2 68 240 006	90	22	85.50	5.4
110	100	10	17/17.6	IR	753 018 639	0.407	2 68 240 006	110	25	104.50	6.6
125	100	10	17/17.6	IR	753 018 515	0.556	2 68 240 022	125	28	116.00	7.3
140	125	10	17/17.6	IR	753 018 516	0.785	2 68 240 022	140	33	131.00	8.2
160	150	10	17/17.6	IR	753 018 517	1.156	2 68 240 022	160	33	151.00	9.4
180	150	10	17/17.6	IR	753 018 518	1.619	2 68 240 022	180	33	171.00	10.6
200	200	10	17/17.6	IR	753 018 519	2.208	2 68 240 022	200	33	190.00	11.7
225	200	10	17/17.6	IR	753 018 520	3.039	2 68 240 022	220	33	210.00	12.9
250	250	10	17/17.6		753 018 521	4.645	2 68 240 002	256	48	232.00	14.2
280	250	10	17/17.6		753 018 522	7.020	2 68 240 002	286	48	262.00	15.9
315	300	10	17/17.6		753 018 523	10.099	2 68 240 002	321	48	297.00	17.9
355	350	10	17/17.6		753 018 524	12.580	2 68 240 040	345	70	330.00	21.1
400	400	10	17/17.6		753 018 525	16.680	2 68 240 040	365	70	350.00	23.7
450	450	10	17/17.6		753 018 526	24.760	2 68 240 040	425	70	400.00	26.7
500	500	10	17/17.6		753 018 527	33.640	2 68 240 040	470	90	445.00	29.7

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 11/2021