


Pevný bod ecoFIT PE100 d63-630 mm / SDR17

Provedení:

- Konvenční svařování natupo dle DVS 2207
- Kompatibilní pro IR = infračervené (IR Plus) svařování. Zvolte svařovací parametry: PE100
- Obráběný



d	DN	PN	SDR	FM	Kód	Váha	D	L	L1	L2	L3	e
(mm)	(mm)	(bar)				(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
63	50	10	17/17.6	IR	753 665 577	0.144	90	122	30	42	10	3.8
75	65	10	17/17.6	IR	753 665 578	0.212	110	122	30	42	10	4.5
90	80	10	17/17.6	IR	753 665 579	0.279	125	122	30	42	10	5.4
110	100	10	17/17.6	IR	753 665 580	0.457	140	142	30	52	15	6.6
125	100	10	17/17.6	IR	753 665 581	0.618	160	152	35	52	15	7.4
140	125	10	17/17.6	IR	753 665 582	0.815	180	162	40	52	15	8.3
160	150	10	17/17.6	IR	753 665 583	1.014	200	162	40	52	15	9.5
180	150	10	17/17.6	IR	753 665 584	1.528	225	182	45	52	20	10.7
200	200	10	17/17.6	IR	753 665 585	1.887	250	182	45	52	20	11.9
225	200	10	17/17.6	IR	753 665 586	2.661	280	192	45	52	25	13.4
250	250	10	17/17.6		753 665 587	2.796	280	212	50	62	25	14.8
280	250	10	17/17.6		753 665 588	3.829	315	222	50	62	30	16.6
315	300	10	17/17.6		753 665 589	4.871	355	222	50	62	30	18.7
355	350	10	17/17.6		753 665 590	5.812	400	192	30	62	35	21.1
400	400	10	17/17.6		753 665 591	8.180	450	212	30	72	40	23.7
450	450	10	17/17.6		753 665 592	11.015	500	232	35	72	45	26.7
500	500	10	17/17.6		753 665 593	15.251	560	252	40	72	50	29.7
560	600	10	17/17.6		753 665 594	21.557	630	282	45	82	55	33.2
630	600	10	17/17.6		753 665 595	29.574	710	302	50	82	60	37.4

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 11/2021