



Koncov° v'í'ko PROGEF Standard S5/SDR11 (PN10)

Proveden'í:

- Materiál: **PP-H**
- Konvenční svařování natupo dle DVS 2207
- Kompatibilní pro IR = Infračervené (IR Plus®) svařování. Zvolte svařovací parametry: PP-H

d (mm)	FM	K ¹ d	V'í'ha (kg)	L (mm)	L1 (mm)	e (mm)
20	IR	727 968 106	0.005	49	42	1.9
25	IR	727 968 107	0.007	52	42	2.3
32	IR	727 968 108	0.016	57	47	2.9
40	IR	727 968 109	0.023	64	51	3.7
50	IR	727 968 110	0.048	72	59	4.6
63	IR	727 968 111	0.087	86	67	5.8
75	IR	727 968 112	0.138	94	73	6.8
90	IR	727 968 113	0.222	112	83	8.2
110	IR	727 968 114	0.375	124	90	10.0
125	IR	727 968 115	0.520	130	94	11.4
140	IR	727 968 116	0.695	142	99	12.7
160	IR	727 968 117	1.040	162	109	14.6
180	IR	727 968 118	1.375	170	113	16.4
200	IR	727 968 119	1.860	179	117	18.2
225	IR	727 968 120	2.625	203	127	20.5

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 11/2018