



Ohyb 90° PROGEF Standard S8.3/SDR17.6

Provedení:

- Materiál: **PP-H**
- Konvenční svařování natupo dle DVS 2207
- Kompatibilní pro infračervené (IR Plus®) svařování, zvolte svařovací parametry PP-H
- * Materiál: PP-R

d (mm)	FM	Kód	Váha (kg)	L (mm)	L1 (mm)	R (mm)	e (mm)
50	IR	727 018 635	0.050	58	21	37	2.9
63	IR	727 018 636	0.081	66	21	45	3.6
75	IR	727 018 637	0.164	100	20	90	4.3
90	IR	727 018 638	0.241	100	20	90	5.1
110	IR	727 018 639	0.484	141	25	130	6.3
125	IR	727 018 415	0.556	125	28	116	7.1
140	IR	727 018 416	0.785	140	33	131	8.0
160	IR	727 018 417	1.156	160	33	151	9.1
180	IR	727 018 418	1.619	180	33	171	10.2
200	IR	727 018 419	2.208	200	33	190	11.4
225	IR	727 018 420	3.039	220	33	210	12.8
250		727 018 421	4.359	256	48	232	14.2
280		727 018 422	6.696	286	48	262	15.9
315		727 018 423	8.580	321	48	297	17.9
* 355		727 018 424	11.640	345	70	330	20.1
* 400		727 018 425	15.200	365	70	350	22.7
* 450		727 018 426	22.240	425	70	400	25.5
* 500		727 018 427	31.020	470	90	445	28.3

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 11/2018