



T-kus 90° PROGEF Standard S8.3/SDR17.6

Provedení:

- Materiál: **PP-H**
- Kompatibilní pro infračervené (IR Plus®) svařování, zvolte svařovací parametry PP-H
- Konvenční svařování natupo dle DVS 2207

¹ Materiál: PP-R

d (mm)	FM	Kód	Váha (kg)	L (mm)	L1 (mm)	e (mm)
50	IR	727 208 410	0.084	92	57	2.9
63	IR	727 208 411	0.172	107	64	3.6
75	IR	727 208 412	0.212	75	20	4.3
90	IR	727 208 413	0.396	90	20	5.1
110	IR	727 208 414	0.705	110	20	6.3
125	IR	727 208 415	1.154	125	50	7.1
140	IR	727 208 416	1.765	160	63	8.0
160	IR	727 208 417	2.335	163	60	9.1
180	IR	727 208 418	4.000	217	97	10.2
200	IR	727 208 419	5.060	220	94	11.4
225	IR	727 208 420	6.870	227	75	12.8
250		727 208 421	7.410	225	67	14.2
280		727 208 422	10.680	266	88	15.9
315		727 208 423	14.105	283	86	17.9
1 355		727 208 424	20.800	345	105	20.1
1 400		727 208 425	27.200	365	105	22.7
1 450		727 208 426	47.300	425	135	26.7
1 500		727 208 427	54.800	470	155	29.7

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.

Přeloženo z originálu výrobce

PPS Engineering CZ s.r.o., zastoupení Georg Fischer Piping Systems

info@ppsengineering.cz

www.ppsengineering.cz

© PPS 11/2018