




COOL-FIT 4.0 Weld-in port PE/Stainless steel With female thread NPT

Model:

- Material: PE100, Stainless steel V4A/ 316L
- With Weld-in port cone (PE100) and female thread NPT (stainless steel) for the installation of sensors, instruments, venting and draining
- Gasket: O-ring EPDM
- Including insulation made from EPDM foam

Note:

For pipes COOL-FIT 4.0 and COOL-FIT 4.0F of the dimensions d63-d225



Size (inch)	Thread	PN (bar)	Code	Weight (kg)	d (mm)	db1 (mm)	D1 (mm)	h1 (mm)	P1 (mm)	z (mm)
1/2	NPT	16	738 113 306	0.148	d63 - d225	11.8	78	85+d/2	15	70 + d/2
3/4	NPT	16	738 113 307	0.191	d63 - d225	17.4	78	85+d/2	16	69 + d/2
1	NPT	16	738 113 308	0.248	d63 - d225	23.1	78	86+d/2	19	67 + d/2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: <http://www.gfps.com>