



Data sheet

valid from: 12/17/21



COOL-FIT 4.0 Pipe d32-d450

Model:

- Pre-insulated PE100 SDR11/17 metric
- Insulation made from GF HE foam
- Impact resistant. Color: black
- Length: 5m for d32-d225, 5.9m for d250-d450
- With free ends for electrofusion

d	d/D	DN	SDR	PN	Code	Weight	di	L	L1	closest inch
(mm)	(mm)	(mm)		(bar)		(kg/m)	(mm)	(mm)	(mm)	(inch)
32	32/90	25	11	16	738 173 108	1.411	26.2	5000	36	1
40	40/110	32	11	16	738 173 109	2.054	32.6	5000	40	1 ½
50	50/110	40	11	16	738 173 110	2.221	40.8	5000	44	1 ½
63	63/125	50	11	16	738 173 111	2.987	51.4	5000	48	2
75	75/140	65	11	16	738 173 112	3.757	61.4	5000	55	2 ½
90	90/160	80	11	16	738 173 113	4.819	73.6	5000	62	3
110	110/180	100	11	16	738 173 114	6.200	90.0	5000	72	4
160	160/250	150	17	10	738 173 117	9.921	141.0	5000	90	6
225	225/315	200	17	10	738 173 120	16.620	198.2	5000	110	8
250	250/355	250	17	10	738 173 021	18.180	220.4	5900	123	10
280	280/400	250	17	10	738 173 022	22.640	246.8	5900	126	10
315	315/450	300	17	10	738 173 023	28.510	277.6	5900	133	12
355	355/500	350	17	10	738 173 024	35.350	312.8	5900	148	14
400	400/560	400	17	10	738 173 125	44.070	352.6	5900	150	16
450	450/630	450	17	10	738 173 126	55.490	396.6	5900	165	18

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>