
Data sheet

valid from: 4/1/26





CONTAIN-IT Plus Mechanical connection PVC-C/PE100
Connections for cementing with Tangit

Model:

- Protective housing PVC-U PN6 / sealing according to inner pipe
- With union PVC-C
- For easy installation and removal

d (mm)	D (mm)	PN (bar)	PN (Outer Pipe) (bar)	SDR	EPDM Code	Weight (kg)	FKM Code	Weight (kg)
20	50	16	6	9	**723 240 106**	4.200	**723 240 126**	4.200
25	50	16	6	9	**723 240 107**	6.500	**723 240 127**	6.500
32	63	16	6	13.6	**723 240 108**	6.600	**723 240 128**	6.600
40	75	16	6	13.6	**723 240 109**	9.300	**723 240 129**	9.300
50	90	16	6	13.6	**723 240 110**	10.300	**723 240 130**	10.300
63	110	16	6	13.6	**723 240 111**	10.100	**723 240 131**	10.100

d (mm)	D1 (mm)	ZA 1 (mm)	ZA 2 (mm)	L1 (mm)	Zi 1 (mm)	Zi 2 (mm)
20	66	255	330	35	289	329
25	66	255	330	41	292	326
32	81	275	355	47	315	348
40	97	325	410	55	369	399
50	118	340	425	65	389	409
63	139	350	480	79	406	457

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com