Data sheet

valid from: 8/18/26




SYGEF Ultra Flange Adaptor flat
PN16
High Purity clean-room product ISO Class 5
Jointing face flat


Model:

- Material: PEEK-HP

d (mm)	DN (mm)	PN (bar)	Code	Weight (kg)
20	15	16	**736 798 006**	0.022
25	20	16	**736 798 007**	0.033
25	20	16	**736 798 557**	0.031
32	25	16	**736 798 008**	0.046
32	25	16	**736 798 558**	0.043
50	40	16	**736 798 010**	0.091
50	40	16	**736 798 560**	0.087
63	50	16	**736 798 011**	0.135
90	80	16	**736 798 013**	0.246
90	80	16	**736 798 563**	0.235
110	100	16	**736 798 014**	0.343
160	150	16	**736 798 017**	0.662



Type A



Type D

d (mm)	DN (mm)	PN (bar)	BD1 (mm)	D1 (mm)	Di1 (mm)	s (mm)	FM	Lmax (mm)	L1 (mm)	Type	Standard	Bm2 (mm)	d4 (mm)	f1 (mm)
20	15	16	27	45	15	1.9	IR	54	6	A	ISO/ANSI	30		
25	20	16	33	58	20	1.9	IR	56	7	D	ISO	30	54	4
25	20	16	33	54	20	1.9	IR	56	7	A	ANSI	30		
32	25	16	40	68	26	1.9	IR	58	7	D	ISO	30	63	4
32	25	16	40	63	26	1.9	IR	58	7	A	ANSI	30		
50	40	16	61	88	44	2.4	IR	69	8	D	ISO	30	82	4
50	40	16	61	82	44	2.4	IR	69	8	A	ANSI	30		
63	50	16	76	102	54	2.5	IR	72	9	A	ISO/ANSI	35		
90	80	16	105	138	78	2.5	IR	81	12	D	ISO	35	133	4
90	80	16	105	133	78	2.5	IR	81	12	A	ANSI	35		
110	100	16	125	158	97	3.1	IR	82	13	A	ISO/ANSI	35		
160	150	16	175	212	150	4.5	IR	94	17	A	ISO/ANSI	40		

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com