Data sheet

valid from: 8/18/26





SYGEF Ultra Flange Adaptor JIS GR
PN16
High Purity clean-room product ISO Class 5
Jointing face with O-Ring groove

Model:

- Material: PEEK-HP

d (mm)	DN (mm)	PN (bar)	Code	Weight (kg)	BD1 (mm)	D1 (mm)	Di1 (mm)	s (mm)	FM	Lmax (mm)	L1 (mm)	Type	Bm2 (mm)
20	15	16	**736 805 206**	0.016	27	34	15	1.9	IR	54	6	E	30
25	20	16	**736 805 207**	0.022	33	41	20	1.9	IR	56	7	E	30
32	25	16	**736 805 208**	0.031	40	50	26	1.9	IR	58	7	E	35
50	40	16	**736 805 210**	0.073	61	73	44	2.4	IR	69	8	E	30
63	50	16	**736 805 211**	0.111	76	90	54	2.5	IR	72	9	E	35
90	80	16	**736 805 213**	0.199	105	125	78	2.5	IR	81	12	E	35
110	100	16	**736 805 214**	0.299	125	150	97	3.1	IR	82	13	E	35

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com