
Data sheet

valid from: 8/18/26





SYGEF Ultra Flange Adaptor groove
PN16
High Purity clean-room product ISO Class 5
Jointing face with O-Ring groove

Model:

- Material: PEEK-HP

d (mm)	DN (mm)	PN (bar)	Code	Weight (kg)
20	15	16	**736 798 206**	0.021
25	20	16	**736 798 207**	0.033
25	20	16	**736 798 757**	0.030
32	25	16	**736 798 208**	0.047
32	25	16	**736 798 758**	0.042
50	40	16	**736 798 210**	0.093
50	40	16	**736 798 760**	0.085
63	50	16	**736 798 211**	0.132
90	80	16	**736 798 213**	0.240
90	80	16	**736 798 763**	0.225
110	100	16	**736 798 214**	0.331
160	150	16	**736 798 217**	0.630

d (mm)	DN (mm)	PN (bar)	BD1 (mm)	D1 (mm)	Di1 (mm)	s (mm)	FM	Lmax (mm)	L1 (mm)	Type	Standard	Bm2 (mm)
20	15	16	27	45	15	1.9	IR	54	6	E	ISO/ANSI	30
25	20	16	33	58	20	1.9	IR	56	7	E	ISO	30
25	20	16	33	54	20	1.9	IR	56	7	E	ANSI	30
32	25	16	40	68	26	1.9	IR	58	7	E	ISO	30
32	25	16	40	63	26	1.9	IR	58	7	E	ANSI	30
50	40	16	61	88	44	2.4	IR	69	8	E	ISO	30
50	40	16	61	82	44	2.4	IR	69	8	E	ANSI	30
63	50	16	76	102	54	2.5	IR	72	9	E	ISO/ANSI	35
90	80	16	105	138	78	2.5	IR	81	12	E	ISO	35
90	80	16	105	133	78	2.5	IR	81	12	E	ANSI	35
110	100	16	125	158	97	3.1	IR	82	13	E	ISO/ANSI	35
160	150	16	175	212	150	4.5	IR	93	17	E	ISO/ANSI	40

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com