




IR PVC-U Flange Adaptor

Combined jointing face flat and serrated metric

Model:

- d20 - d50: Sealing surface flat
- d63: combined jointing face flat and serrated
- For welding on IR-63 Plus and IR-110 A
- Special Clamping inserts needed on IR-63 Plus and IR-110 A
- Only use Tangit KS Cleaner (799298023)

d	DN	PN	SDR	Code	Weight	s	Lmax	Bm2	L1	D1	BD1	Di1
(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
20	15	16	9	721 798 106	0.024	2.3	54	35	6.0	45	26	14.5
25	20	16	13.6	721 798 107	0.037	1.9	56	35	6.5	58	32	20.0
32	25	16	13.6	721 798 108	0.051	2.4	58	35	7.0	63	40	26.0
40	32	16	13.6	721 798 109	0.076	3.0	68	45	7.5	73	49	33.0
50	40	16	13.6	721 798 110	0.117	3.7	69	45	8.0	88	40	41.0
63	50	16	13.6	721 798 111	0.180	4.7	72	45	9.0	102	75	52.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>