




ecoFIT Tee 90° reduced PE100
d63-250mm / SDR11

Model:

- Conventional butt-welding according to DVS 2207
- IR = Infrared-(IR Plus) compatible. Choose fusion parameters: PE100



d	d2	DN	PN	FM	Code	Weight	Lmax	s1	s2	z1	z2	Bm1	Bm2
(mm)	(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
63	32	50	16	IR	753 208 351	0.161	130.0	5.8	2,9	65	70	25	25
63	50	50	16	IR	753 208 352	0.180	130.0	5.8	4,6	65	70	25	25
75	32	65	16	IR	753 208 353	0.255	140.0	6.8	2,9	70	75	25	25
75	50	65	16	IR	753 208 354	0.265	140.0	6.8	4,6	70	75	25	25
75	63	65	16	IR	753 208 355	0.278	140.0	6.8	5,8	70	75	25	25
90	50	80	16	IR	753 208 357	0.435	160.0	8.2	4,6	80	85	25	25
90	63	80	16	IR	753 208 358	0.448	160.0	8.2	5,8	80	85	25	25
90	75	80	16	IR	753 208 359	0.462	160.0	8.2	6,8	80	85	25	25
110	32	100	16	IR	753 208 360	0.685	180.0	10.0	2,9	90	95	30	25
110	50	100	16	IR	753 208 361	0.694	180.0	10.0	4,6	90	95	30	25
110	63	100	16	IR	753 208 362	0.709	180.0	10.0	5,8	90	95	30	25
110	75	100	16	IR	753 208 363	0.717	180.0	10.0	6,8	90	95	30	25
110	90	100	16	IR	753 208 364	0.734	180.0	10.0	8,2	90	95	30	25
160	63	150	16	IR	753 208 371	2.269	284.0	14.6	5,8	142	135	50	30
160	75	150	16	IR	753 208 372	2.255	284.0	14.6	6,8	142	135	50	30
160	90	150	16	IR	753 208 373	2.317	284.0	14.6	8,2	142	135	50	30
160	110	150	16	IR	753 208 374	2.353	284.0	14.6	10,0	142	135	50	30
225	90	200	16	IR	753 208 388	4.759	310.0	20.5	8,2	155	165	40	30
225	110	200	16	IR	753 208 389	4.796	310.0	20.5	10,0	155	165	40	30
225	160	200	16	IR	753 208 391	4.854	310.0	20.5	14,6	155	165	40	30

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>