



ecoFIT outlet flange adaptor PE100
d40-315mm / SDR17/17.6

Model:

- Conventional butt-welding according to DVS 2207
- Suitable for wafer check valves Type 369

Attention:

- In conjunction with Outlet flange adaptors, **flange rings for socket systems** must be used.

d	DN	PN	SDR	Code	Weight	D	D1	D2	L	L1	L2	e	r
(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
40	32	10	17/17.6	733 808 009	0.060	80	37	50	64	30	11	2.3	3
50	40	10	17/17.6	733 808 010	0.067	90	43	61	67	30	12	2.9	3
63	50	10	17/17.6	733 808 011	0.159	105	54	76	74	30	14	3.6	4
75	65	10	17/17.6	733 808 012	0.219	125	70	90	78	30	16	4.3	4
90	80	10	17/17.6	733 808 013	0.314	140	82	108	87	35	17	5.1	4
110	100	10	17/17.6	733 808 014	0.465	160	105	131	102	41	18	6.3	4
140	125	10	17/17.6	733 808 016	0.862	190	130	165	124	47	18	8.0	4
160	150	10	17/17.6	733 808 017	1.176	215	158	188	149	52	18	9.1	4
225	200	10	17/17.6	733 808 020	2.484	270	206	248	180	55	24	12.8	4
280	250	10	17/17.6	733 808 022	2.230	325	259	308	240	63	25	15.9	4
315	300	10	17/17.6	733 808 023	2.450	375	308	346	272	66	25	17.9	4

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>