



ecoFIT Adaptor socket PE100

d20-63mm / SDR11 / Female thread Rp / With butt fusion spigot

Model:

- With butt fusion spigot **SDR11** and BSP parallel female thread Rp, reinforced
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Do not use thread sealing pastes that are harmful to PE
- Install with low mechanical stress and avoid large cyclic temperature changes

d	SDR	PN	Gewindetyp	Size	DN	FM	Code	Weight	L	L1	s	e
(mm)		(bar)		(inch)	(mm)			(kg)	(mm)	(mm)	(mm)	(mm)
20	11	16	Rp	½	15	IR	753 910 266	0.018	49	23	32	1.9
25	11	16	Rp	¾	20	IR	753 910 267	0.022	51	23	36	2.3
32	11	16	Rp	1	25	IR	753 910 268	0.038	55	23	46	3.0
40	11	16	Rp	1 ¼	32	IR	753 910 269	0.068	57	23	55	3.7
50	11	16	Rp	1 ½	40	IR	753 910 270	0.083	60	23	64	4.6
63	11	16	Rp	2	50	IR	753 910 271	0.134	62	23	80	5.8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>