



ecoFIT Adaptor socket PE100 NPT d20-63mm / SDR11

Model:

- Conventional butt-welding according to DVS 2207
- IR = Infrared-(IR Plus) compatible. Choose fusion parameters: PE100
- NPT tapered female thread to ASTM F 1498
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Do not use thread sealing pastes that are harmful to PE
- Install with low mechanical stress and avoid large cyclic temperature changes

d	SDR	PN	Gewindetyp	Size	DN	FM	Code	Weight	L	L1	s	e
(mm)		(bar)		(inch)	(mm)			(kg)	(mm)	(mm)	(mm)	(mm)
20	11	16	NPT	1/2	15	IR	753 914 266	0.018	48	23	32	1.9
25	11	16	NPT	3/4	20	IR	753 914 267	0.022	50	23	36	2.3
32	11	16	NPT	1	25	IR	753 914 268	0.038	54	23	46	2.9
40	11	16	NPT	1 1/4	32	IR	753 914 269	0.058	56	23	55	3.7
50	11	16	NPT	1 1/2	40	IR	753 914 270	0.083	60	23	65	4.6
63	11	16	NPT	2	50	IR	753 914 271	0.134	62	23	80	5.8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>