



ecoFIT Union end PE100 d20-110mm / SDR11

Model:

- Conventional butt-welding according to DVS 2207
- IR = Infrared- (IR Plus) compatible.

*Only for variable area flow meters

d	DN	PN	FM	Code	Weight	Do	s1	Z	Bm1
(mm)	(mm)	(bar)			(kg)	(mm)	(mm)	(mm)	(mm)
20	15	16	IR	753 508 606	0.011	30.0	1.9	54	38
25	20	16	IR	753 508 607	0.018	39.0	2.3	57	42
32	25	16	IR	753 508 608	0.027	45.0	2.9	60	41
40	32	16	IR	753 508 609	0.044	57.0	3.7	63	42
50	40	16	IR	753 508 610	0.061	63.0	4.6	66	44
63	50	16	IR	753 508 611	0.100	78.0	5.8	69	45
75	65	10	IR	753 508 212	0.144	101.5	6.8	66	34
*	75	65	10	700 246 420	0.300	101.0	6.8	66	34
90	80	10	IR	753 508 213	0.158	101.5	8.2	65	55
110	100	10	IR	753 508 214	0.230	121.0	10.0	65	55

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>