



ELGEF Plus Branch saddle topload PE100
d450-1000mm / SDR11 / Outlet 315 mm

- 10 bar Gas / 16 bar Water
- Branch saddle installation only with installation set Topload TL500 (799.300.809)
- Angle adaptors (799.350.340) for fusion cable required
- 4 mm pin connectors
- Spigot outlet for butt- and electrofusion
- Full pressure applicable - no derating factor
- With integrated thread for pressure test with separate pressure test cap 799.199.288 (outlet d315) / 799.199.289 (outlet d500)

d (mm)	d1 (mm)	SDR	PN (bar)	DN (mm)	Code	Weight (kg)
450	315	11	16	450	193 135 436	18.500
500	315	11	16	500	193 135 446	17.000
560	315	11	16	600	193 135 456	16.100
630	315	11	16	600	193 135 466	15.950
710	315	11	16	700	193 135 476	14.800
800	315	11	16	800	193 135 486	14.300
900	315	11	16	900	193 135 496	13.800
1000	315	11	16	1000	193 135 506	13.500

d (mm)	d1 (mm)	d2 (mm)	D (mm)	L (mm)	L1 (mm)	h (mm)	H (mm)	SDR pipe
450	315	232	500	500	174	346	216	11 - 26
500	315	232	500	500	174	337	216	11 - 26
560	315	232	500	500	174	327	216	11 - 26
630	315	232	500	500	174	312	216	11 - 33
710	315	232	500	500	174	297	216	11 - 33
800	315	232	500	500	174	287	216	11 - 33
900	315	232	500	500	174	281	216	11 - 33
1000	315	232	500	500	174	274	216	11 - 33

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>