



L = length / Länge

ELGEF Plus Stop-off saddle (kit) PE100
d63-400mm / SDR11 / Maximum passage 56.5 mm

- 10 bar Gas / 16 bar Water
- Complete with lower part
- Stop-Off insert (CW617N) and plug
- 4 mm pin connectors
- Limited path fusion indicators
- Stop-Off insert with outside thread Rp 2 1/2" and internal thread Rp 2" suited for common tapping devices permitting "gas-tight" installation
- We recommend the following maximum cutting diameter: For main dimension d63 and d75mm: d = 39mm; For main dimension d90mm: d = 50mm
- * Topload: delivery without lower part for assembling as Top Load with tool no. 799.350.477; angle adaptor (799.350.340) for fusion cable required

	d SDR		DN	PN	Rp	Code	Weight	L SDR pipe	
	(mm)		(mm)	(bar)	(inch)		(kg)	(mm)	
	63	11	50	10	2 ½	193 149 437	1.770	165	9 - 11
	75	11	65	10	2 ½	193 149 447	1.900	165	9 - 11
	90	11	80	10	2 ½	193 149 457	1.775	165	9 - 11
	110	11	100	10	2 ½	193 149 467	1.788	165	9 - 17.6
	125	11	100	16	2 ½	193 149 477	1.923	165	9 - 17.6
	140	11	125	16	2 ½	193 149 487	1.945	165	9 - 17.6
	160	11	150	16	2 ½	193 149 497	1.861	165	9 - 17.6
	180	11	150	16	2 ½	193 149 507	2.017	165	9 - 26
	200	11	200	16	2 ½	193 149 517	2.092	165	9 - 26
	225	11	200	16	2 ½	193 149 527	2.031	165	9 - 26
	250	11	250	16	2 ½	193 149 537	2.058	165	9 - 26
*	280	11	250	16	2 ½	193 149 547	1.550	165	9 - 26
*	315 - 355	11	300 - 350	16	2 ½	193 149 557	1.770	165	9 - 33
*	400	11	400	16	2 ½	193 149 577	1.550	165	9 - 33

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>