


Data sheet

valid from: 8/27/21



ELGEF Plus Transition elbow 90° PE/brass d20-63mm / SDR11 / Male thread R

- 10 bar Gas / 16 bar Water
- With integral pipe fixation
- 4 mm pin connectors
- Limited path fusion indicators
- Supplied as a kit

d	DN	Thread Type	Size	PN	SDR	Code	Weight	d1	L	s	SDR pipe
(mm)	(mm)		(inch)	(bar)			(kg)	(mm)	(mm)	(mm)	
20	15	R	½	16	11	720 100 756	0.240	31	96	30	9-11
25	20	R	¾	16	11	720 100 757	0.260	36	97	35	9-11
32	25	R	1	16	11	720 100 758	0.368	44	98	40	9-11
32	25	R	1 ¼	16	11	720 100 766	0.500	44	100	50	9-11
32	25	R	1 ½	16	11	720 100 767	0.562	44	100	60	9-11
40	32	R	1	16	11	720 100 771	0.511	54	107	50	9-11
40	32	R	1 ¼	16	11	720 100 759	0.534	54	109	50	9-11
40	32	R	1 ½	16	11	720 100 772	0.615	54	109	60	9-11
50	40	R	1	16	11	720 100 776	0.677	66	116	60	9-11
50	40	R	1 ¼	16	11	720 100 777	0.771	66	118	60	9-11
50	40	R	1 ½	16	11	720 100 760	0.734	66	118	60	9-11
63	50	R	1 ¼	16	11	720 100 782	1.040	81	128	70	9-17.6
63	50	R	1 ½	16	11	720 100 783	1.039	81	128	70	9-17.6
63	50	R	2	16	11	720 100 761	1.108	81	132	70	9-17.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>