



**ELGEF Plus Transition elbow 90° PE/stainless steel
d20-63mm / SDR11 / Male thread R**

- 10 bar Gas / 16 bar Water
- With integral pipe fixation
- 4 mm pin connectors
- Limited path fusion indicators
- Supplied as a kit

d	DN	Thread Type	Size	PN	SDR	Code	Weight	d1	L	s	SDR pipe
(mm)	(mm)		(inch)	(bar)			(kg)	(mm)	(mm)	(mm)	
20	15	R	½	16	11	724 100 756	0.211	31	96	30	9-11
25	20	R	¾	16	11	724 100 757	0.230	36	97	35	9-11
32	25	R	1	16	11	724 100 758	0.324	44	98	40	9-11
40	32	R	1 ¼	16	11	724 100 759	0.560	54	109	50	9-11
50	40	R	1 ½	16	11	724 100 760	0.701	66	118	60	9-11
63	50	R	2	16	11	724 100 761	1.105	81	132	70	9-17.6

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>