



Profiled Backing Flanges Metal, Epoxy coated

Model:

- Ductile iron (GGG 40), stoved epoxy (black, DIN30677)
- Metric: ISO 7005, EN 1092, ISO 9624

Note:

Flat side = bolt / washer side

Profiled side = flange adaptor side (aligned with collar)

AL: number of holes

d (mm)	DN (mm)	PN (bar)	Standard	Bolt / circle	Design	Code	Weight (kg)
125	125	16	Metric	PN10	Butt	701 474 386	6.000
450	450	10	Metric	PN10	Butt	724 705 026	38.000
450	500	10	Metric	PN16	Butt	724 705 326	50.500
500	500	10	Metric	PN16	Butt	724 705 327	50.500
560	600	10	Metric	PN16	Butt	724 705 328	50.500
630	600	10	Metric	PN16	Butt	724 705 329	50.500
710	700	6	Metric	PN10	Butt	724 705 130	36.400
800	800	6	Metric	PN10	Butt	724 705 131	50.500
900	900	6	Metric	PN10	Butt	724 705 132	55.800
1000	1000	6	Metric	PN10	Butt	724 705 133	71.100
1200	1200	6	Metric	PN10	Butt	724 705 134	101.000

D (mm)	D1 (mm)	D2 (mm)	D3 (mm)	H (mm)	AL	SC
250	210	135	18	25	8	M16
615	565	470	26	36	20	M24
715	650	517	33	46	20	M30
715	650	533	33	46	20	M30
840	770	618	36	55	20	M33
840	770	645	36	55	20	M33
900	840	740	30	45	24	M27
1015	950	843	33	53	24	M30
1115	1050	947	33	56	28	M30
1230	1160	1050	36	62	28	M33
1455	1380	1260	39	68	32	M36

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>