



Type A




Type B




Type C




Type A



Type B



Type C



PROGEF Plus Flange adaptor SDR11 (PN10) combined jointing face: flat and serrated

Model:

- Material: PP-H
- Conventional butt-welding according to DVS 2207
- IR- Infrared welding compatible
- Suitable for flange connections to metric (from d110 also to ANSI/ASME B16.5)
- Suitable for butterfly valve type 567/578 and 038/039
- Gasket: profile flange gasket EPDM No. 48 44 17, FKM No. 49 44 17
- Cleaned and double bagged

d (mm)	SDR	DN (mm)	PN (bar)	FM	Code	Weight (kg)
20	11	15	10	IR	727 798 731	0.015
25	11	20	10	IR	727 798 732	0.028
32	11	25	10	IR	727 798 733	0.042
40	11	32	10	IR	727 798 734	0.064
50	11	40	10	IR	727 798 735	0.094
63	11	50	10	IR	727 798 736	0.144
75	11	65	10	IR	727 798 737	0.243
90	11	80	10	IR	727 798 738	0.330
110	11	100	10	IR	727 798 739	0.444
125	11	100	10	IR	727 798 740	0.520
140	11	125	10	IR	727 798 741	0.800
160	11	150	10	IR	727 798 772	0.927
180	11	150	10	IR	727 798 773	1.026
200	11	200	10	IR	727 798 774	1.652
225	11	200	10	IR	727 798 775	1.700
250	11	250	10		727 798 776	2.630
280	11	250	10		727 798 777	2.784
315	11	300	10		727 798 778	3.410

d (mm)	d1 (mm)	d2 (mm)	d3 (mm)	d4 (mm)	L (mm)	L1 (mm)	L2 (mm)	e (mm)	Type	a°
20	26	45		16	50	29	7	1.9	A	
25	32	58		20	52	27	9	2.3	A	
32	40	68		26	54	28	10	2.9	A	
40	49	78		32	56	25	11	3.7	A	
50	60	88		40	62	32	12	4.6	A	
63	75	102		51	68	38	14	5.8	A	
75	89	122	66	61	80	43	16	6.8	B	30
90	105	138	78	73	80	41	17	8.2	B	30
110	125	158	100	90	80	40	18	10.0	B	30
125	132	158	114	102	82	35	25	11.4	B	25
140	155	188	127	114	89	39	25	12.7	B	27
160	175	212	151	127	92	40	25	14.6	C	30
180	180	212	154	148	92	40	30	17.5	B	30
200	232	268	203	174	100	35	32	19.3	C	30
225	235	268	210	196	100	35	32	21.7	C	30
250	285	320	252	203	120	45	35	24.0	C	25
280	291	320	265	228	120	45	37	26.8	C	30
315	335	370	300	256	150	50	50	30.2	C	22

Data sheet

valid from: 3/2/23



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>