



PROGEF Standard Adaptor nipple
Metric NPT female SDR11 (PN10)

Model:

- Material: PP-H
- With butt fusion spigot **SDR11** and NPT tapered female thread, reinforced
- Reinforcing ring stainless (A2)
- Connection to plastic or metal threads
- Do not use thread sealing pastes that are harmful to PP
- Install with low mechanical stress and avoid large cyclic temperature changes

d	Thread Type	Size	PN	SDR	FM	Code	SP	Weight	L	L1	s	e
(mm)		(inch)	(bar)					(kg)	(mm)	(mm)	(mm)	(mm)
20	NPT	½	10	11	IR	727 914 356	10	0.017	49	23	32	1.9
25	NPT	¾	10	11	IR	727 914 357	10	0.022	51	23	36	2.3
32	NPT	1	10	11	IR	727 914 358	10	0.039	54	23	46	2.9
40	NPT	1 ¼	10	11	IR	727 914 359	10	0.057	56	23	55	3.7
50	NPT	1 ½	10	11	IR	727 914 360	10	0.085	60	23	65	4.6
63	NPT	2	10	11	IR	727 914 361	5	0.122	62	23	80	5.8

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>