




Solenoid pilot valve type PV96 3/2 way valve for single acting actuators

- Connections/Position: 3/2 way pilot valve
- Functionality: normally closed
- Orifice Size: 2.0 mm
- Power: 7 watts
- Housing Material: PPS
- Seal Material: FKM
- Coil Material: Epoxy Resin, Insulation Class H
- Coil Approval: UL recognized (USA & Canada, cURus)
- Media: Neutral gases and liquids
- Viscosity: Max. 21 mm²/s
- Media Temperature: 10 °C to +40 °C
- Ambient Temperature: 10 °C to +40 °C
- Manual Override: Yes
- Nominal Operation Mode: Continuous Duty 100 % ED
- Protection Class: IP 65 with plug connector
- Electrical Connection: According to DIN EN 175301-803 Form B



Voltage	Port P	Port A	DN (mm)	Qn Value air [l/min]	Code	Weight (kg)
24 V/ DC	NPT 1/8	G 1/8, G 1/4	2	75	199 196 100	0.145
24 V/ DC	G 1/8	G 1/8, G 1/4	2	75	199 196 101	0.145
24 V/ AC	NPT 1/8	G 1/8, G 1/4	2	75	199 196 102	0.145
24 V/ DC	G 1/8 Push-in 6mm	G 1/8, G 1/4	2	75	199 196 103	0.145
24 V/ AC	G 1/8 Push-in 6mm	G 1/8, G 1/4	2	75	199 196 104	0.145
110V/ AC	G 1/8 Push-in 6mm	G 1/8, G 1/4	2	75	199 196 105	0.145
120V/ AC	NPT 1/8	G 1/8, G 1/4	2	75	199 196 106	0.145
230V/ AC	G 1/8 Push-in 6mm	G 1/8, G 1/4	2	75	199 196 107	0.145
230V/ AC	G 1/8	G 1/8, G 1/4	2	75	199 196 108	0.145

Length (mm)	Width (mm)	Height (mm)
76.0	24.4	65
60.0	24.4	65
76.0	24.4	65
60.0	24.4	65
78.9	24.4	65
78.9	24.4	65
76.0	24.4	65
78.9	24.4	65
60.0	24.4	65

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>