

Data sheet

valid from: 10/13/26





1



PROGEF Standard Tee 90° reduced
SDR11/PN10

Model:

- Material: PP-H
- Conventional butt-welding according to DVS 2207
- IR = Infrared welding compatible

[1]with IR welded reducer

	d (mm)	d1 (mm)	PN (bar)	FM	Code	Weight (kg)	L (mm)	L1 (mm)	L2 (mm)	L3 (mm)	e (mm)	e1 (mm)
1	63	25	10	IR	**727 208 356**	0.190	65	112	25	20.0	5.8	2.3
	63	32	10	IR	**727 208 351**	0.161	65	70	25	25.0	5.8	2.9
	63	40	10	IR	**727 208 350**	0.165	65	70	25	25.0	5.8	3.7
	63	50	10	IR	**727 208 352**	0.170	65	70	25	25.0	5.8	4.6
	75	32	10	IR	**727 208 353**	0.238	70	75	25	25.0	6.8	2.9
	75	50	10	IR	**727 208 354**	0.249	70	75	25	25.0	6.8	4.6
	75	63	10	IR	**727 208 355**	0.258	70	75	25	25.0	6.8	5.8
1	90	32	10	IR	**727 208 071**	0.470	80	142	25	20.0	8.2	2.9
	90	50	10	IR	**727 208 357**	0.420	80	85	25	25.0	8.2	4.6
	90	63	10	IR	**727 208 358**	0.428	80	85	25	25.0	8.2	5.8
	90	75	10	IR	**727 208 359**	0.430	80	85	25	25.0	8.2	6.8
	110	32	10	IR	**727 208 360**	0.652	90	95	30	25.0	10.0	2.9
	110	50	10	IR	**727 208 361**	0.659	90	95	30	25.0	10.0	4.6
	110	63	10	IR	**727 208 362**	0.665	90	95	30	25.0	10.0	5.8
	110	75	10	IR	**727 208 363**	0.681	90	95	30	25.0	10.0	6.8
	110	90	10	IR	**727 208 364**	0.701	90	95	30	25.0	10.0	8.2
	125	63	10	IR	**727 208 665**	1.680	125	230	25	16.0	11.4	5.8
1	125	90	10	IR	**727 208 066**	1.700	125	225	25	40.0	11.4	8.2
1	125	110	10	IR	**727 208 367**	1.700	125	217	25	30.0	11.4	10.0
1	140	75	10	IR	**727 208 068**	2.400	140	245	28	41.0	12.7	6.8
1	140	90	10	IR	**727 208 069**	2.358	140	240	28	40.0	12.7	8.2
1	140	110	10	IR	**727 208 370**	2.380	140	242	28	33.0	12.7	10.0
	160	63	10	IR	**727 208 371**	2.130	142	135	50	30.0	14.6	5.8
	160	75	10	IR	**727 208 372**	2.143	142	135	50	30.0	14.6	6.8
	160	90	10	IR	**727 208 373**	2.148	142	135	50	30.0	14.6	8.2
	160	110	10	IR	**727 208 374**	2.186	142	135	50	30.0	14.6	10.0
	160	125	10	IR	**727 208 075**	3.600	160	272	28	32.0	14.6	11.4
1	180	63	10	IR	**727 208 077**	6.640	215	299	97	28.0	16.4	6.2
1	180	110	10	IR	**727 208 078**	6.490	215	355	97	40.0	16.4	10.0
1	200	160	10	IR	**727 208 385**	6.632	200	332	35	40.0	18.2	14.6
	200	180	10	IR	**727 208 086**	6.900	200	335	35	45.0	18.2	16.4
	225	90	10	IR	**727 208 388**	4.576	155	165	40	30.0	20.5	8.2
	225	110	10	IR	**727 208 389**	4.624	155	165	40	30.0	20.5	10.0
	225	160	10	IR	**727 208 391**	4.685	155	165	40	30.0	20.5	14.6
	250	160	10	IR	**727 208 093**	12.500	227	387	68	53.0	22.7	14.6
1	315	110	10	IR	**727 208 079**	26.460	283	416	86	29.5	28.6	10.6
1	315	160	10	IR	**727 208 080**	26.950	283	421	86	37.5	28.6	15.4
1	315	225	10	IR	**727 208 081**	25.440	283	508	86	60.0	28.6	20.5
1	315	250	10	IR	**727 208 082**	25.440	283	502	86	63.0	28.6	22.7

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com