



Barrel nipple PVC-U metric



Model:

- With solvent cement spigots on both sides
- Overall length L = 2 x socket length
- For the shortest possible distance between fittings

d	Size	PN	d	Code	Weight	L
(mm)	(inch)	(bar)	(inch)		(kg)	(mm)
16		16		721 900 905	0.002	28
20		16		721 900 906	0.005	32
25		16		721 900 907	0.009	38
32		16		721 900 908	0.015	44
40		16		721 900 909	0.027	52
50		16		721 900 910	0.048	62
63		16		721 900 911	0.092	76
75	2 ½	16	2 ½	721 900 912	0.156	88
90		16		721 900 913	0.260	102
110		16		721 900 914	0.455	122
125		16		721 900 915	0.673	138
140	5	16	5	721 900 916	0.932	152
160		16		721 900 917	1.565	192
200		10		721 900 919	1.779	212
225		10		721 900 920	2.566	238

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>