# Data sheet

valid from: 4/4/26






## Barrel nipple PVC-U metric /british standard (BS)

**Model:**

- With solvent cement spigots on both sides
- Overall length L = 2 x socket length
- For the shortest possible distance between fittings

| | d (mm) | Size (inch) | PN (bar) | Code | Weight (kg) | L (mm) |
|---|---|---|---|---|---|---|
| metric | 16 | | 16 | **721 900 905** | 0.002 | 28 |
| metric | 20 | | 16 | **721 900 906** | 0.005 | 32 |
| metric | 25 | | 16 | **721 900 907** | 0.009 | 38 |
| metric | 32 | | 16 | **721 900 908** | 0.015 | 44 |
| metric | 40 | | 16 | **721 900 909** | 0.027 | 52 |
| metric | 50 | | 16 | **721 900 910** | 0.048 | 62 |
| metric | 63 | | 16 | **721 900 911** | 0.092 | 76 |
| metric/ BS | 75 | 2 ½ | 16 | **721 900 912** | 0.156 | 88 |
| metric | 90 | | 16 | **721 900 913** | 0.260 | 102 |
| metric | 110 | | 16 | **721 900 914** | 0.455 | 122 |
| metric | 125 | | 16 | **721 900 915** | 0.673 | 138 |
| metric/ BS | 140 | 5 | 16 | **721 900 916** | 0.932 | 152 |
| metric | 160 | | 16 | **721 900 917** | 1.565 | 192 |
| metric | 200 | | 10 | **721 900 919** | 1.779 | 212 |
| metric | 225 | | 10 | **721 900 920** | 2.566 | 238 |
| BS | | ⅜ | 16 | **721 901 905** | 0.002 | 29 |
| BS | | ½ | 16 | **721 901 906** | 0.004 | 33 |
| BS | | ¾ | 16 | **721 901 907** | 0.008 | 39 |
| BS | | 1 | 16 | **721 901 908** | 0.015 | 45 |
| BS | | 1¼ | 16 | **721 901 909** | 0.027 | 54 |
| BS | | 1½ | 16 | **721 901 910** | 0.050 | 60 |
| BS | | 2 | 16 | **721 901 911** | 0.098 | 72 |
| BS | | 3 | 16 | **721 901 913** | 0.226 | 101 |
| BS | | 4 | 16 | **721 901 914** | 0.476 | 126 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com