
# Data sheet

valid from: 3/31/26






## Tee 90° equal PVC-U metric / BS

| | d (mm) | d (inch) | PN (bar) | Size (inch) | Code | SP | Weight (kg) | D (mm) | L (mm) | z (mm) |
|---|---|---|---|---|---|---|---|---|---|---|
| | 6 | | 16 | | **721 200 101** | 10 | 0.004 | 11 | 16 | 4 |
| | 8 | | 16 | | **721 200 102** | 10 | 0.008 | 13 | 17 | 5 |
| | 10 | | 16 | | **721 200 103** | 10 | 0.008 | 16 | 18 | 6 |
| | 12 | | 16 | | **721 200 104** | 10 | 0.011 | 19 | 19 | 7 |
| | 16 | | 16 | | **721 200 105** | 10 | 0.011 | 21 | 23 | 9 |
| | 20 | | 16 | | **721 200 106** | 10 | 0.019 | 25 | 27 | 11 |
| | 25 | | 16 | | **721 200 107** | 10 | 0.029 | 31 | 33 | 14 |
| | 32 | | 16 | | **721 200 108** | 10 | 0.055 | 38 | 39 | 17 |
| | 40 | | 16 | | **721 200 109** | 10 | 0.100 | 48 | 49 | 23 |
| | 50 | | 16 | | **721 200 110** | 10 | 0.156 | 58 | 57 | 26 |
| | 63 | | 16 | | **721 200 111** | 10 | 0.291 | 73 | 71 | 33 |
| * | 75 | 2 ½ | 16 | 2 ½ | **721 200 112** | 5 | 0.476 | 87 | 83 | 39 |
| | 90 | | 16 | | **721 200 113** | 4 | 0.824 | 105 | 97 | 46 |
| | 110 | | 16 | | **721 200 114** | 6 | 1.411 | 127 | 116 | 55 |
| | 125 | | 16 | | **721 200 115** | 2 | 2.521 | 151 | 135 | 66 |
| * | 140 | 5 | 16 | 5 | **721 200 116** | 4 | 3.410 | 169 | 147 | 71 |
| | 160 | | 16 | | **721 200 117** | 4 | 4.982 | 193 | 167 | 81 |
| | 200 | | 10 | | **721 200 119** | 1 | 5.868 | 225 | 207 | 101 |
| | 225 | | 10 | | **721 200 120** | 1 | 9.268 | 256 | 233 | 114 |
| | 250 | | 10 | | **721 200 121** | 1 | 14.350 | 282 | 263 | 132 |
| | 280 | | 10 | | **721 200 122** | 1 | 19.541 | 318 | 298 | 152 |
| | 315 | | 6 | | **721 200 123** | 1 | 27.254 | 356 | 332 | 168 |
| | 400 | | 6 | | **721 200 125** | 1 | 35.000 | 442 | 420 | 214 |
| | | | 15 | ⅜ | **721 201 105** | 10 | 0.018 | 25 | 25 | 10 |
| | | | 15 | ½ | **721 201 106** | 10 | 0.036 | 30 | 30 | 13 |
| | | | 15 | ¾ | **721 201 107** | 10 | 0.051 | 35 | 37 | 16 |
| | | | 15 | 1 | **721 201 108** | 10 | 0.079 | 43 | 43 | 19 |
| | | | 15 | 1 ¼ | **721 201 109** | 10 | 0.105 | 50 | 51 | 22 |
| | | | 15 | 1 ½ | **721 201 110** | 5 | 0.157 | 57 | 56 | 26 |
| | | | 15 | 2 | **721 201 111** | 5 | 0.294 | 72 | 68 | 32 |
| | | | 15 | 3 | **721 201 113** | 5 | 0.847 | 107 | 97 | 46 |
| | | | 15 | 4 | **721 201 115** | 8 | 1.864 | 138 | 122 | 59 |
| | | | 15 | 6 | **721 201 117** | 1 | 5.674 | 202 | 176 | 86 |
| | | | 9 | 8 | **721 201 120** | 1 | 10.742 | 256 | 233 | 114 |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com