
Data sheet

valid from: 3/28/26





Pipe PVC-U transparent
SDR21 /Series S10

Model:

- Material: PVC-U
- Dimension: acc. to DIN 8062
- Colour: transparent - Transparency depends on outer diameter and wall thickness! Chemical and thermical stress can cause discolouration
- Pipe length: 5000mm, with plain ends
- Approval: food grade, with declaration of conformity acc. EU 10/2011 and EU 1953/2004, Approval on request
- Attention: Pressure rates refer to operating temperatures at 20°C. Higher temperatures and aggressive flow media reduce pressure load (see above DIN and our technical documentation). Pressure load capacity has to be determined in consideration with safety demands of the respective applications and calculated in accordance.
- * SDR17
- * pcs in foil

	d (mm)	SDR	PN (bar)	Code	Weight (kg/m)	e (mm)	di (mm)
* 20	25	17	10	**192 017 082**	0.177	1.5	22.0
* 10	32	17	10	**192 017 083**	0.280	1.9	28.4
* 10	40	21	10	**192 017 084**	0.355	1.9	36.2
* 5	50	21	10	**192 017 085**	0.560	2.4	45.2
* 3	63	21	10	**192 017 086**	0.866	3.0	57.0
* 3	75	21	10	**192 017 087**	1.240	3.6	67.8
* 2	90	21	10	**192 017 088**	1.770	4.3	81.4
* 1	110	21	10	**192 017 089**	2.650	5.3	99.4

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/SwitzerlandPhone +41 -(0)52-631 1111e-mail: info.ps@georgfischer.comInternet: http://www.gfps.com