



## Plug PVC-U G

### Model:

- With parallel male thread G
- Flat gasket necessary for sealing
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U

| G      | PN    | Code               | SP | Weight | L    | s    |
|--------|-------|--------------------|----|--------|------|------|
| (inch) | (bar) |                    |    | (kg)   | (mm) | (mm) |
| 3/8    | 10    | <b>721 960 905</b> | 10 | 0.005  | 21   | 22   |
| 1/2    | 10    | <b>721 960 906</b> | 10 | 0.010  | 25   | 27   |
| 3/4    | 10    | <b>721 960 907</b> | 10 | 0.018  | 29   | 36   |
| 1      | 10    | <b>721 960 908</b> | 10 | 0.029  | 32   | 41   |
| 1 1/4  | 10    | <b>721 960 909</b> | 10 | 0.048  | 36   | 50   |
| 1 1/2  | 10    | <b>721 960 910</b> | 10 | 0.070  | 37   | 60   |
| 2      | 10    | <b>721 960 911</b> | 5  | 0.120  | 42   | 75   |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>