



## Adaptor union PVC-U/stainless steel metric R

### Model:

- Union Nut: PVC-U
- Union Bush: Solvent cement socket PVC-U metric
- Union End: Stainless Steel 1.4404 (316L), taper male thread R
- Gasket: O-ring EPDM code no. 748 410 005-011

| d<br>(mm) | Thread Type | Size<br>(inch) | PN<br>(bar) | EPDM<br>Code | FKM<br>Code | SP | Weight<br>(kg) | SP | Weight<br>(kg) |
|-----------|-------------|----------------|-------------|--------------|-------------|----|----------------|----|----------------|
| 16        | R           | 3/8            | 16          | 721 540 705  | 721 540 730 | 10 | 0.073          | 0  | 0.073          |
| 20        | R           | 1/2            | 16          | 721 540 706  | 721 540 731 | 10 | 0.126          | 10 | 0.126          |
| 25        | R           | 3/4            | 16          | 721 540 707  | 721 540 732 | 10 | 0.174          | 5  | 0.170          |
| 32        | R           | 1              | 16          | 721 540 708  | 721 540 733 | 5  | 0.262          | 10 | 0.262          |
| 40        | R           | 1 1/4          | 16          | 721 540 709  | 721 540 734 | 2  | 0.476          | 1  | 0.472          |
| 50        | R           | 1 1/2          | 16          | 721 540 710  | 721 540 735 | 2  | 0.535          | 1  | 0.535          |
| 63        | R           | 2              | 16          | 721 540 711  | 721 540 736 | 2  | 0.934          | 1  | 0.931          |

| d<br>(mm) | G<br>(inch) | z<br>(mm) | D<br>(mm) | L<br>(mm) | L1<br>(mm) | L2<br>(mm) | s<br>(mm) |
|-----------|-------------|-----------|-----------|-----------|------------|------------|-----------|
| 16        | 3/8         | 40        | 35        | 54        | 30         | 24         | 19        |
| 20        | 1           | 44        | 43        | 60        | 34         | 26         | 24        |
| 25        | 1 1/4       | 46        | 51        | 65        | 36         | 29         | 32        |
| 32        | 1 1/2       | 50        | 58        | 72        | 40         | 33         | 37        |
| 40        | 2           | 58        | 72        | 84        | 46         | 39         | 48        |
| 50        | 2 1/4       | 62        | 83        | 93        | 48         | 46         | 54        |
| 63        | 2 3/4       | 73        | 100       | 111       | 55         | 58         | 69        |

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>