



SYGEF Plus Flange adaptor with jointing face serrated ISO SDR21/PN16
High Purity clean-room product ISO Class 5 (100)

Model:

- Material: PVDF-HP

d (mm)	DN (mm)	PN (bar)	FM	Type	Code	Weight (kg)
20	15	16	BCF, IR	A	735 798 831	0.029
25	20	16	BCF, IR	B	735 798 832	0.044
32	25	16	BCF, IR	B	735 798 833	0.070
40	32	16	BCF, IR	B	735 798 834	0.096
50	40	16	BCF, IR	B	735 798 835	0.136
63	50	16	BCF, IR	A	735 798 836	0.198
75	65	16	BCF, IR	A	735 798 837	0.311
90	80	16	BCF, IR	B	735 798 838	0.387
110	100	16	BCF, IR	C	735 798 839	0.555
140	125	16	IR	C	735 798 841	0.887
160	150	16	IR	C	735 798 842	1.171
200	200	16	IR	C	735 798 844	2.139
225	200	16	IR	C	735 798 845	2.064
250	250	16	IR	C	735 798 846	3.658
280	250	16	IR	C	735 798 847	3.586
315	300	16	IR	C	735 798 848	5.028

d (mm)	L (mm)	L1 (mm)	L2 (mm)	D (mm)	D1 (mm)	D2 (mm)	D3 (mm)	e (mm)	SP	GP
20	54	6		26	45	15		1.9	1	25
25	56	7	4	32	58	20	54	1.9	1	15
32	58	7	4	40	68	26	63	2.4	1	20
40	68	8	4	49	78	34	73	2.4	1	10
50	69	8	4	60	88	43	82	3.0	1	10
63	72	9		75	102	56		3.0	1	15
75	80	10		89	122	66		3.6	1	12
90	81	12	4	105	138	78	133	4.3	1	5
110	81	13		125	158	100		5.3	1	4
140	90	16		155	188	127		6.7	1	5
160	93	17		175	212	151		7.7	1	5
200	102	22		232	268	207		9.6	1	4
225	102	22		235	268	207		10.8	1	4
250	122	25		285	320	249		11.9	1	1
280	122	25		291	320	249		13.4	1	1
315	124	28		335	370	300		15.0	1	1

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>