



SYGEF Standard adaptor nipple male thread NPT SDR21/PN16

Model:

- Material: PVDF
- With butt fusion spigot and tapered male thread
- Avoid stresses when installing and large changes in temperature
- Connection to plastic thread only
- Do not use thread sealing pastes that are harmful to PVDF

d	Size	PN	FM	Thread Type	Code	Weight	L	L1	s	e
(mm)	(inch)	(bar)				(kg)	(mm)	(mm)	(mm)	(mm)
20	¾	16	BCF, IR	NPT	735 914 555	0.024	50	26	32	1.9
20	½	16	BCF, IR	NPT	735 914 556	0.025	53	26	32	1.9
25	¾	16	BCF, IR	NPT	735 914 557	0.035	55	26	36	1.9
32	1	16	BCF, IR	NPT	735 914 558	0.053	57	26	46	2.4
40	1 ¼	16	BCF, IR	NPT	735 914 559	0.075	60	26	55	2.4
50	1 ½	16	BCF, IR	NPT	735 914 560	0.122	63	26	65	3.0
63	2	16	BCF, IR	NPT	735 914 561	0.176	69	27	75	3.0

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>