



Quick Connect Valve 700 (QC7) Swiveled end-connection: NPT 1"

The QC7 utilizing two full bore ball valves that only allow flow when both valves are open. The patented interlock design ensures that the valve cannot be disconnected while it is under pressure.

Model:


- Dual interlock lever mechanism
- 360° swiveled end-connections
- Color coding: Blue for supply // Red for return
- Fluid loss: Approx 5,5cc.
- Valve body: PVDF
- Lever: PP-GF30
- Ball seat: PTFE
- O-Rings: EPDM
- Face seal: EPDM
- Protection cap

Note:

Standards: EN ISO 9393


Option:

- Further connections on request.



	DN	Size	Di	Do	DE	PN	kv-value ($\Delta p=1$ bar)	Cv 100 (gal/min)	EPDM Code	SP	Weight (kg)
	(mm)	(inch)	(mm)	(mm)	(mm)	(bar)	(L/min)				
NPT - Blue	25	1	28	42	70	10	570	39	735 911 700	1	0.750
NPT - Red	25	1	28	42	70	10	570	39	735 911 702	1	0.750

	DN	L1	L2	M1-1	M2-1	Lmax	Hmax	Wopen	Wclosed
	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		
NPT - Blue	25	96.0	96.0	26.5	46	192.0	102	79.5	85.5
NPT - Red	25	96.0	96.0	26.5	46	192.0	102	79.5	85.5



The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>