



Quick Connect Valve 700 (QC7) Swiveled end-connection: NPT 1"

Model:



- Dual interlock lever mechanism
- 360° swiveled end-connections
- Color coding: Blue for supply // Red for return
- Fluid loss: Approx 5,5cc.
- Valve body: PVDF
- Lever: PP-GF30
- Ball seat: PTFE
- O-Rings: EPDM
- Face seal: EPDM
- Protection cap

Note:

Standards: EN ISO 9393

Option:

- Further connections on request.



	DN	Size	Di	Do	DE	PN	kv-value	Cv 100	EPDM	SP	Weight
	(mm)	(inch)	(mm)	(mm)	(mm)	(bar)	($\Delta p=1$ bar)	(gal/min)	Code		(kg)
							(L/min)				
NPT - Blue	25	1	28.0	42.0	70	10	570	39	735 911 701	1	0.380
NPT - Red	25	1	28.0	42.0	70	10	570	39	735 911 703	1	0.380

	DN	L1	M1-1	M2-1	Lmax	Hmax	Wopen	Wclosed
	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)		
NPT - Blue	25	96.0	26.5	46	109.0	85.5	79.5	85.5
NPT - Red	25	96.0	26.5	46	109.0	85.5	79.5	85.5

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail:
info.ps@georgfischer.com Internet: <http://www.gfps.com>