Data sheet


valid from: 8/17/26



SYGEF Ultra Flare Transition Fitting
PN16
High Purity clean-room product ISO Class 5

Model:

- Material: PEEK-HP



d (mm)	DN (mm)	PN (bar)	Code	Weight (kg)	Bm1 (mm)	DE2 (mm)	FM	Lmax (mm)	s (mm)	Suitable for
20	15	16	**736 598 006**	0.015	30.0	20.5	IR	74.6	1.9	1/4" Inch
25	20	16	**736 598 007**	0.017	30.0	20.5	IR	74.6	1.9	1/4" Inch
20	15	16	**736 598 016**	0.017	30.0	23.1	IR	76.2	1.9	3/8" Inch
25	20	16	**736 598 017**	0.019	30.0	23.1	IR	76.2	1.9	3/8" Inch
25	20	16	**736 598 026**	0.019	30.0	26.2	IR	76.5	1.9	1/2" Inch
20	15	16	**736 598 027**	0.021	30.0	26.2	IR	76.5	1.9	1/2" Inch
32	25	16	**736 598 028**	0.024	30.0	26.2	IR	76.5	1.9	1/2" Inch
20	15	16	**736 598 036**	0.033	29.7	33.8	IR	77.6	1.9	3/4" Inch
25	20	16	**736 598 037**	0.030	30.0	33.8	IR	77.6	1.9	3/4" Inch
32	25	16	**736 598 038**	0.032	30.0	33.8	IR	77.6	1.9	3/4" Inch
25	20	16	**736 598 047**	0.066	30.3	45.7	IR	87.3	1.9	1" Inch
32	25	16	**736 598 048**	0.060	30.3	45.7	IR	87.3	1.9	1" Inch

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland Phone +41 -(0)52-631 1111 e-mail: info.ps@georgfischer.com Internet: http://www.gfps.com